

RFID-метка Balluff BIS U-102-05/CA-HT

Код заказа : BIS00WC

Ключевые особенности

Series	BIS U (UHF, 865-928MHz)
Size	128x52x11,5 mm
Memory capacity read-only	64 Bit TID, incl. 32 Bit SID
Memory capacity read/write	240 Bit EPC
Ambient temperature	-40...+85 °C
Enclosure Type per IEC 60529	IP68

Общие свойства

Enclosure Type per IEC 60529	IP68
Additional text	<p>Time specification includes data check. For application conditions refer to corresponding read/write head. Only when used together with the appropriate read/write head. Values are under rated conditions unless otherwise specified. For installation in metal: Observe clear zone. For mounting the data carrier on flat metal surfaces use spacer.</p>
Series	BIS U (UHF, 865-928MHz)

Электрические параметры

Memory capacity read/write	240 Bit EPC
Memory capacity read-only	64 Bit TID, incl. 32 Bit SID
Data retention time / years	≥ 50
Read cycles	Unlimited
Frequency range	860 ... 960 MHz
Polarization	linear

Механические параметры

Housing material	PPS NATURAL
Ambient temperature Ta min.	-40 °C
Ambient temperature Ta max.	+85 °C
Storage temperature	-40 °C ... +220 °C
Shock rating	EN 60068 Part 2-27
Vibration rating	EN 60068 Part 2-6
Continuous shock load	EN 60068 Part 2-29
Free fall	EN 60068 Part 2-32
Application weight	70 g