

SMART-I-MINI-TAG

Small size, excellent performance on metal surfaces.



SMARTRAC Smart-i-Mini-Tags are the right choice for applications where the size of the transponder is decisive.

With its small diameter and a thickness of ca 1 millimeter, the tag can be easily integrated into OEM equipment such as medical devices to enable maintenance and warranty follow up, or into high-value assets to prove genuineness.

SMARTRAC Smart-i-Mini-Tags are ideal for integration into client specific applications. The tags are manufactured by epoxy encapsulation which is suited for the production of very small tags and offers reliable protection from moisture and other outside interference.

The Smart-i-Mini-Tag 6 mm tags have been specifically developed for direct use of RFID technology on metallic surfaces. The excellent reading performance of the 6 mm tag is achieved by means of an integrated absorber foil.

Benefits:

- ▶ Small size.
- ▶ Easy integration into OEM equipment.
- ▶ Excellent performance.
- ▶ Directly attachable to metal surfaces.

Overview

Operating Frequency
13.56 MHz

Integrated Circuit (IC)
NXP ICode SLIX

Tag Size
Ø 6 mm (0.24 in)

International Standards
ISO 15693
ISO 18000-3
IP67

Operating Temperature
0 to 50°C / 32 to 122°F

Quality Assurance
100% performance tested

Application Areas

- ▶ Very small tools
- ▶ Medical devices
- ▶ Delicate objects such as cosmetic bottles

SMART-I-MINI-TAG

Technical Features	
IC	NXP ICode SLIX
Memory	1k bit
Frequency	13.56 MHz
Tag Size	Ø 6 mm / 0.24"
Thickness	1.05 mm / 0.04"
Hole Diameter	N/A
Operating Temperature	0°C to 50°C / 32°F to 122°F
Storage Temperature	-20°C to 90°C / -4°F to 194°F (max 168h)
Material	Epoxy resin
Color	Black
IP Class	IP67
Qty/Package	1,000 tags / box
Shelf Life: minimum of 2 years from the date of manufacture in	20°C / 68°F, 50% RH



RoHS CE

For further information, please contact our sales representatives:

Sales Europe

SMARTRAC TECHNOLOGY GROUP
Hanauer Landstrasse 291a
60314 Frankfurt am Main
Germany
Tel. +49 69 904 3579 1011
Fax +49 69 904 3579 1015
sales.emea@smartrac-group.com

Sales Americas

SMARTRAC TECHNOLOGY Fletcher Inc.
267 Cane Creek Road
Fletcher, NC 28732
United States of America
Tel. +1 866 901 7343
Fax +1 828 651 6063
sales.americas@smartrac-group.com

Sales APAC

SMARTRAC TECHNOLOGY PTE. Ltd.
SINGAPORE
6 Greenleaf Walk
Amsterdam Building 2-8
Singapore 279226
Tel. +60 4 489 36-0
Fax +60 4 489 36-50
sales.apac@smartrac-group.com

© 2013 SMARTRAC N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.