




UHF Special Tags

Product Description	Product Code	Picture	Operating Frequency (MHz)	Dimension	Encasement	EPC-USER memory	Read Range	Features
RFID Seal Tag	TR36013		860-960 MHz	320X24X8 mm	Polypropylene	96 - 512 bits	3-4 meters	It can be used to track logistics information and animals. The rfid tag is non-dismountable
Asset Management Tag	TR36003		860-960 MHz	102X22X6 mm	ABS	96 - 512 bits	4 meters	IP classification: IP67 Supporting components: Silicone sealants 3M 300LSE acrylic adhesive Personalization options: Customer Logo
Indoor On-Metal Tag	TR36035		860-960 MHz	60X12X2.8 mm	Resin	96 - 512 bits	3 meters	Has a unique ID and can store additional information. It can stick on the shelves and IT metal products. The appearance and special LOGO can be customized based on customer requirements
Indoor On-Metal Tag	TR36026		860-960 MHz	75x15x2.8 mm	Resin	96 - 512 bits	4 meters	
Indoor On-Metal Tag	TR36030		860-960 MHz	100x30x2.8 mm	Resin	96 - 512 bits	5 meters	
Outdoor On-Metal Tag	TR36029		860-960 MHz	103x24x6.8 mm	FR4	96 - 512 bits	3 meters	FR4 casing material, multiple fixture methods including: hang, stick, and lanyard etc. Can be used in metal environment.
Outdoor On-Metal Tag	TR36032		860-960 MHz	117x32x7.6 mm	FR4	96 - 512 bits	5 meters	FR4 casing material, multiple fixture methods including: hang, stick, and lanyard etc. Can be used in metal environment.