


Модели и комплекты PowerScan PD9500	
PowerScan D9530 High Performance 10-30VDC	PD9530-HPE
PowerScan D9530 High Performance 5VDC	PD9530-HP
PowerScan D9530 Standard 5VDC	PD9530
СОГЛАШЕНИЯ	
MINIMUM REPAIR CHARGE,PD95XX SR	ZR0PD95MIN
PowerScan 95XXSR EofC 2 Days Comprehensive, 1 Year Renewal	ZSC2PD95C1
PowerScan 95XXSR EofC 2 Days Comprehensive, 3 Years	ZSC2PD9531
PowerScan 95XXSR EofC 2 Days Comprehensive, 5 Years	ZSC2PD9551
PowerScan 95XXSR EofC 5 Days, 1 Year Renewal	ZSN5PD95C1
PowerScan 95XXSR EofC 5 Days, 3 Years	ZSN5PD9531
PowerScan 95XXSR EofC 5 Days, 5 Years	ZSN5PD9551
PowerScan 95XXSR EofC Overnight Replacement Comprehensive, 1 Year Renewal	ZSC1PD95C1
PowerScan 95XXSR EofC Overnight Replacement Comprehensive, 3 Years	ZSC1PD9531
PowerScan 95XXSR EofC Overnight Replacement Comprehensive, 5 Years	ZSC1PD9551
WHOLE UNIT REPAIR,PD95XX SR	ZR0PD95MAX
КАБЕЛИ	
Cable, IBM USB, 12 VDC, Powers USB, Coiled, 15 ft, CAB-486	CAB-486
Cable, KBW 3151, 347x, 378x, Coiled, CAB-485, 11 ft.	CAB-485
Cable, KBW, PS/2, Coiled, CAB-437, 9 ft.	CAB-437
Cable, KBW, PS/2, External Power, Coiled, CAB-443	CAB-443
Cable, KBW, PS/2, External Power, Straight, CAB-442	CAB-442
Cable, KBW, PS/2, Laptop, Coiled, 3.6 m, CAB-463	CAB-463
Cable, KBW, PS/2, PWR, Coiled 3.6 m, CAB-462	CAB-462
Cable, KBW, PS/2, Straight, CAB-436, 6 ft.	CAB-436
Cable, RS-232 PWR, 25P, Female, Coiled, 3.6 m, CAB-474	CAB-474
Cable, RS-232 PWR, 25P, Female, Coiled, 7.6 m, CAB-477	CAB-477
Cable, RS-232 PWR, 9P, Female, Coiled, 3.6 m, CAB-459	CAB-459
Cable, RS-232 PWR, 9P, Female, Coiled, CAB-434, 8 ft.	CAB-434
Cable, RS-232 PWR, 9P, Female, Straight, 3.2 m, CAB-501	CAB-501
Cable, RS-232 PWR, 9P, Female, Straight, CAB-433, 6 ft.	CAB-433
Cable, RS-232, 25P, Female, Coiled, CAB-471, 10 ft.	CAB-471
Cable, RS-232, 25P, Male, CBX800 Power Off Terminal, Coiled, 12 ft.	CAB-512
Cable, RS-232, 25P, Male, CBX800, External Power, Coil, 12 ft	CAB-509
Cable, RS-232, 25P, Male, Coiled, CAB-472, 10 ft.	CAB-472
Cable, RS-232, 9D, Female, POT, Coiled, 25 ft, 90A052014, CAB-479	CAB-479
Cable, RS-232, 9P, Female, Straight, CAB-448, 6 ft.	CAB-448
Cable, RS-232, 9P, Male, Coiled, 3.6 m, CAB-456	CAB-456
Cable, RS-232, RJ10 Magellan Bi-Optic AUX Port, Coiled, 3.6 m, CAB-461, 12 ft.	CAB-461

	Cable, USB, Type A, Coiled, 3.6 m, CAB-467, 12 ft.	CAB-467
	Cable, USB, Type A, Coiled, POT, CAB-524, 8 ft.	CAB-524
	Cable, USB, Type A, External Power, Coiled, CAB-441, 8 ft.	CAB-441
	Cable, USB, Type A, External Power, Straight, CAB-440, 8 ft.	CAB-440
	Cable, USB, Type A, Straight, 3.6 m, CAB-465	CAB-465
	Cable, USB, Type A, Straight, CAB-438, 6.5 ft.	CAB-438
КОРПУС/КОБУРА		
	Настольный/настенный держатель	HLD-P080
	Подогреваемый корпус, 24VDC (Для моделей без дисплея)	11-0139
	Подогреваемый корпус, 36VDC (Для моделей без дисплея)	11-0138
	Подогреваемый корпус, 48VDC (Для моделей без дисплея)	11-0140
	Универсальная кобура, HLS-8000	HLS-P080
	Защитный кожух/Кобура для ремня, PC-8000 (для моделей с дисплеем)	PC-P080
УСТАНОВОЧНЫЕ КОМПЛЕКТЫ/СТЕНДЫ		

	Индустриальный установочный комплект	7-0404
ИСТОЧНИКИ ПИТАНИЯ/СИЛОВЫЕ КАБЕЛИ		
Adapter, Power Plug, Australia (Use with 4004-0849)	6003-0939	
Adapter, Power Plug, Euro (Use with 4004-0849)	6003-0937	
Adapter, Power Plug, UK (Use with 4004-0849)	6003-0938	
Adapter, Power Plug, US/Japan (Use with 4004-0849)	6003-0936	
Power Cord, 2-Pin, EU	90ACC1885	
Power Cord, 2-Pin, UK	90ACC1887	
Power Cord, 2-Pin, US	90ACC1886	
Power Supply, 12VDC, PG12-10P55 (For Use with 90ACCXXXX Power Cords Sold Separately)	90ACC1883	
Power Supply, 12VDC, US, PG12-10P55-US (includes power cord 90ACC1886)	90ACC1920	
Power Supply, 5VDC, ROHS (Power Adapter Sold Separately.)	4004-0849	