

<i>Motorola MC 1000</i>	
MC1000-KU0LF2K000R	Batch device, Mono 240x240, Non-Touch, 1D Laser SE950, 32MB RAM/64MB Flash, English CE 5.0 Core, Wrist Strap
MC1000-KU0LF2K00CR	Batch device, Mono 240x240, Non-Touch, 1D Laser SE950, 32MB RAM/64MB Flash, Simplified Chinese CE 5.0 Core, Wrist Strap
MC1000-KU0LF2K00KR	Batch device, Mono 240x240, Non-Touch, 1D Laser SE950, 32MB RAM/64MB Flash, Korean CE 5.0 Core, Wrist Strap
<i>Motorola MC 1000 Accessories</i>	
CRD1000-1000ES	Single Slot Serial/USB Cradle with Spare Battery Charging. Includes PS (PWRS-14000-249R). Order separately, 2 wire ungrounded AC line cord (for US AC line cord order 50-16000-182R) and USB cable (25-68596-01R) or RS232
25-68596-01R	USB Client Communication Cable for Cradle to the host system.
25-63852-01R	RS232 Cable for cradle to the host system. Provides serial communication between the Single Slot Serial/USB cradle and a host computer.
BTRY-MC10EAB00	LiON 1800 mAh Rechargeable battery (Does not require separate battery charger, charges while MC1000 is in cradle)
SSB-MC1000-30	3 Year Service from the Start Service Center Bronze. Includes Comprehensive Coverage. Does not include coverage for cradles.